

**In the Claims**

1. (Cancelled)

2. (Currently amended) ~~[[A]]~~ The method according to claim 11 wherein the said thread is arranged to contain code for performing the defragmentation of the data.

3. (Currently amended) ~~[[A]]~~ The method according to claim 11 wherein the said thread is arranged to contain code for causing a further code to perform the defragmentation of the data.

4. (Currently amended) ~~[[A]]~~ The method according to claim 11 wherein the said thread comprises a thread of operating system code for causing the computing device to adopt a reduced power mode by placing a central processing unit of the computing device into a standby mode, thereby to further reduce the power consumer from the power resources of the computing device.

5. (Currently amended) ~~[[A]]~~ The method as claimed in claim 11 wherein the said thread comprises ~~[[the]]~~ a thread which is arranged to be ~~[[the]]~~ a first thread to run at boot time of the computing device.

6. (Currently amended) ~~[[A]]~~ The method according to claim 11 wherein the computing device is selected to comprise a wireless information device.

Claims 7 to 10 (Cancelled)

11. (Previously presented) A method of managing in a computing device the use of random access memory arranged in the form of a plurality of blocks and used to store data in the form of a plurality of frame pages, the method comprising using a thread of operating system code which is arranged to run on the computing device when no other thread is ready to run to initiate defragmentation of the data, and characterised by restricting defragmentation of the data to when it is determined that the frame pages of data after defragmentation can be held in a reduced number of blocks of memory in comparison to prior to defragmentation, thereby to reduce the number of blocks of the memory used to store the frame pages of data and requiring to be refreshed, and thereby reduce the power consumed from the power resources of the computing device to store the said data.

12. (Currently amended) A computing device programmed to ~~operate according to the method of claim 11~~ manage the use of the computing device's random access memory (RAM), said RAM being arranged in the form of a plurality of blocks and used to store data in the form of a plurality of frame pages, comprising:

means for initiating defragmentation of the data using a thread of operating system code arranged to run on the computing device when no other thread is ready to run;

means for restricting defragmentation of the data to when it is determined that the frame pages of data after defragmentation can be held in a reduced number of blocks of memory in comparison to prior to defragmentation, thereby reducing the number of blocks of the memory

used to store the frame pages of data and in need of being refreshed, and thereby reducing the power consumed by power resources of the computing device to store the said data.

13. (Currently amended) ~~Computer~~ A computer program product embodied on a computer-readable medium, comprising computer software arranged on said computer-readable medium to cause a computing device to operate according to ~~[[a]] the method according to any of claim 11 when executed on said computing device.~~